

Isocell GmbH & Co KG
 Gewerbestraße 9
 A-5202 Neumarkt am Wallersee
 Tel +43 (0)6216 41 08 - 0
 Fax +43 (0) 6216 79 79
 office@isocell.at
 www.isocell.com

1. Unique identifying code of the product type	ÖKO NATUR Vapour Retarder fabric-reinforced
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4)	Mentioned on the container or the printing
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	EN 13984 Flexible sheets for waterproofing - Plastic and rubber vapour control layers
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	Isocell GmbH & Co KG Gewerbestraße 9 A- 5202 Neumarkt am Wallersee
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	./.
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 3
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard	Die notifizierte Stelle Materialprüfanstalt (MPA) Braunschweig, Beethovenstr.52, D-38106 Braunschweig; Nr.0761-CDP hat die Feststellung des Produkttyps anhand einer Typenprüfung nach dem System 3 vorgenommen und Folgendes ausgestellt: Prüfbericht Nr. 5277/388/09.
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	./.

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Length	50 / 50 / 50 m	EN 13984: 2013
Width	1 / 1,5 / 3 m	
Weight	175 g/m²	
Water vapour transmission properties	6.45 m	
Material composition	Two layers of kraft paper with tear-resistant fabric between	
Elongation - lengthwise	≥ 4 %	
Elongation - crosswise	≥ 7,5 %	
Tensile strength - lengthwise	≥ 580 N / 50 mm	
Tensile strength - crosswise	≥ 390 N / 50 mm	
Tear propagation resistance - lengthwise	≥ 80 N	
Tear propagation resistance - crosswise	≥ 90 N	
Fire performance	E	
Fire performance	EN 13501_1 / EN 11925_2	
After artificial aging		
Age resistance	bestanden	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

Spitaler Anton (Managing Director)
(Name and function)

Neumarkt a.W. 11/04/2023
(Place and date of issue)



(Signature)