Declaration of Performance DoP No. DB/42/1/1/1



Isocell GmbH & Co KG Gewerbestraße 9 A-5202 Neumarkt am Wallersee Tel +43 (0)6216 41 08 - 0 Fax +43 (0) 6216 79 79 office@isocell.at www.isocell.com

OMEGA ALUBIT SK Vapour Barrier
Mentioned on the container or the printing
Isocell GmbH & Co KG Gewerbestraße 9 A- 5202 Neumarkt am Wallersee
/.
System 3
nicht relevant
./.
)

CE



9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Length	25 m	
Width	1,08 m	
Weight	650 g/m²	

Water vapour transmission properties	$1500 \ge m$	
Material composition	Aluminium composite foil with reinforcement of glass fibre. Cold bitumen coating.	a
Elongation - lengthwise	≥ 2 %	DIN EN 13970: 2004
Elongation - crosswise	≥ 2 %	-
Tensile strength - lengthwise	≥ 800 N / 50 mm	-
Tensile strength - crosswise	≥ 800 N / 50 mm	-
Shearing resistance of the connection joints	≥ 200 N / 50 mm	-
Fire performance	E	-
Fire performance	EN 13501_1 / EN 11925_2	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

Spri lahr

Spitaler Anton (Managing Director) (Name and function)

Neumarkt a.W. 11/04/2023 (Place and date of issue) (Signature)

