

Isocell GmbH & Co KG
Gewerbstraße 9
A-5202 Neumarkt am Wallersee
Tel +43 (0)6216 41 08 - 0
Fax +43 (0) 6216 79 79
office@isocell.at
www.isocell.com

1. Unique identifying code of the product type	OMEGA DRAINY PLUS Roof Underlay
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4)	Mentioned on the container or the printing
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer	EN 13859-1 (2010): Flexible sheets for waterproofing. Part 1: Underlays for discontinuous roofing
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5)	Isocell GmbH & Co KG Gewerbstraße 9 A- 5202 Neumarkt am Wallersee
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2)	./.
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V	System 3
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard	Prüfinstitut SKZ- TeConA GmbH (Identifikationsnummer1213) hat die Feststellung des Produkttyps (EN 13859) anhand einer Typprüfung nach dem System 3 vorgenommen.
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued	./.

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Length	25 m	
Width	1,5 m	
Weight	450 ($\pm 5\%$) g/m ²	
Water vapour transmission properties	0.02 m	
Material composition	3-layer PP fleece with 3-dimensional PP mesh fabric	
Resistance to water flow	W1	
Elongation - lengthwise	50 - 60 %	
Elongation - crosswise	50 - 60 %	
Tensile strength - lengthwise	295 (± 40) N / 50 mm	
Tensile strength - crosswise	205 (± 40) N / 50 mm	EN 13859-1
Tear propagation resistance - lengthwise	185 (± 30) N	
Tear propagation resistance - crosswise	230 (± 30) N	
Fire performance	E	
Fire performance	EN 13501_1 / EN 11925_2	
After artificial aging		
Tensile strength - lengthwise	240 ($\pm 15\%$) N / 50 mm	
Tensile strength - crosswise	160 ($\pm 15\%$) N / 50 mm	
Resistance to water flow	W1	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

Spitaler Anton (Managing Director)
(Name and function)



Neumarkt a.W. 11/04/2023
(Place and date of issue)

(Signature)