



PRODUCT DATA SHEET

ISOWINDOW FEBA SOFT WS

The window tape two-way consists of a fleece structure that can be plastered over and is coated with a high-performance adhesive. The back is completely adhesive and has split liners. The adhesive strip covering the surface can be attached directly to the window frame without detaching a liner and the tape is completely concealed when embedded.

FIELD OF APPLICATION

- for window installation

ADVANTAGES

- „fingerlift“
- soft flexible structure
- extremely strong adhesion on all types of window frame and various substrates e.g. concrete, plaster, OSB, wood, vapour barriers...
- alternating adhesive coating for concealed fitting
- split liners
- flexibility for movement of building component
- can be plastered and painted over

STANDARDS

Meets the requirements of the following standards

- DIN 4108-11 including Aging
- DIN 4108-7
- ÖNORM B 8110-2
- ÖNORM B 5320
- SIA 180
- RAL-compliant

AVAILABLE IN THE FOLLOWING DIMENSIONS

Type	WS	WS
Roll width	75 mm	100 mm
Roll length	25 m	25 m
Split liner	25/50	35/65
Carton	6 Rollen	4 Rollen

PRODUCT DATA

Material composition	Flexible fleece, laminated air-tight
Colour	White
sd-value	7 m
Temperature resistance	-40 °C - 80 °C
UV-resistance	6 months
Working temperature	-5 °C - 40 °C
Storage	12 months; cool and dry

ISOWINDOW FEBA SOFT WS

INFO

ISOWINDOW FEBA SOFT WS is attached to the window frame before the window is installed. The fleece side of the tape can be plastered and painted over. The adhesive side is attached to the wall, wood, OSB or vapour barrier.

(1)

The fleece side of ISOWINDOW is covered with a narrow acrylic adhesive strip that can be attached directly to the window frame without removing a liner.

(2)

Lay the window frame with the inside facing upwards. Press the mounting strip carefully onto the window frame. Roll the ISOWINDOW along as far as the corner.





(3)

Make a fold at the corners. Do this by pressing the window tape firmly as far as the corners of the window frame, push the material along and make a fold. These 'corners' are to ensure tightness at the corners.

(4)

When the window tape is attached to the entire window frame and the joint insulated, pull off the wide masking paper and press onto the window frame.

The more pressure applied, the better the adhesion (AIRSTOP ROLL Pressing Roller, AIRSTOP RAK Plastic Squeegee)!



ISOCELL GmbH & Co KG

Gewerbstraße 9
5202 NEUMARKT AM WALLERSEE | Österreich
Tel.: +43 6216 4108
office@isocell.at

ISOCELL SCHWEIZ AG

Herbergstrasse 29
9524 ZUZWIL | Suisse /Schweiz
Tel.: +41 71 940 06 72
office@isocell.ch

ISOCELL FRANCE

170 Rue Jean Monnet | ZAC de Prat Pip Sud
29490 GUIPAVAS | France
Tél.: +33 2 98 42 11 00
contact@isocell-france.fr

ISOCELL BUREEL BELGIË

Außenborner Weg 1 | Schoppen
4770 AMEL | Belgique
Tel.: +32 80 39 90 58
office@isocell.be

ISOCELL Sverige AB

Torshamnsgatan 35
164 40 KISTA | Sverige
Tel.: +46 10 130 25 00
info@isocell.se

ISOCELL
www.isocell.com