Technical data sheet

AIRSTOP ELASTO Sealing Patches

To guarantee air and wind-tightness for the skin of a construction it must have the appropriate foils or panel materials providing a permanent seal at overlaps, gaps, joints and penetration points. AIRSTOP ELASTO Sealing Plaster is tear-resistant with adhesive generously applied, with strong adhesion.

Advantages

- quick and easy application
- strong adhesion

Field of application

- a quick seal for larger openings e.g. blow-in openings

Standards

- DIN 4108-11 including Aging
- DIN 4108-7
- ÖNORM B 8110-2
- SIA 180

Available dimensions

Article number	Width	Length	Piece / roll	Carton
3APELDP	180 mm	180 mm	250 pieces	5 rolls

Technical data

Material composition	PE base material with polyester fabric and acrylate adhesive	Temperature resistance	-40–80 °C
Working temperature	-5–40 °C	Shelf life	2 years
Colour	Green transparent with black inprint	Storage	cool and dry
Outdoor exposure	2 months		

ISOCELL GmbH & Co KG
Gewerbestraße 9
5202 Neumarkt am Wallersee
+43 6216 4108
office@isocell.at

ISOCELL France
170 Rue Jean Monnet
29490 Guipavas
+33 2 98 42 11 00
contact@isocell-france.fr

ISOCELL Sverige AB
Torshamnsgatan 35
164 40 Kista
+46 10-130 25 01
info@isocell.se

ISOCELL Schweiz AG
Bahnhofstrasse 6
9201 Gossau SG
+41 71 940 06 72
office@isocell.ch

ISOCELL Bureel België
Außenborner Weg 1
4770 Amel
+32 80 39 90 58
office@isocell.be

ISOCELL
www.isocell.com

06_2026_EN

Processing Guideline

AIRSTOP ELASTO Sealing Patches

Info

The materials used must be free from dust and grease and substrates must be dry and supporting. The greater the pressure applied, the better the performance of the adhesive tape. Sealing Plaster has the function of sealant and not of a firm connector (No permanent tensile stresses may act on the bonded joints – e.g. if the drill cores of OSB boards are re-inserted, they must be mechanically fixed). The pure acrylate adhesive used does not contain resins or other additives that could cause the adhesive film to become brittle and therefore this product is extremely resistant to ageing.

ISOCELL GmbH & Co KG
Gewerbestraße 9
5202 Neumarkt am Wallersee
+43 6216 4108
office@isocell.at

ISOCELL France
170 Rue Jean Monnet
29490 Guipavas
+33 2 98 42 11 00
contact@isocell-france.fr

ISOCELL Sverige AB
Torshamnsgatan 35
164 40 Kista
+46 10-130 25 01
info@isocell.se

ISOCELL Schweiz AG
Bahnhofstrasse 6
9201 Gossau SG
+41 71 940 06 72
office@isocell.ch

ISOCELL Bureel België
Außenborner Weg 1
4770 Amel
+32 80 39 90 58
office@isocell.be

ISOCELL
www.isocell.com

06_2026_EN