

Technical data sheet



## AIRSTOP GD2 Conduit Sleeve

To enable vapour retarders and other materials to fulfil their purpose as airtight layer in a construction these must have air-tight joints at openings for conduits. Warm air finds its way inside a building component through even the smallest of holes in the vapour retarder, where it then condenses. AIRSTOP Conduit Sleeves, bonded air-tight with age-resistant sealing plasters, guarantee that the construction is wind-tight and air-tight

### ADVANTAGES

- extremely flexible
- resistant to ageing
- integrated sealing plaster for air-tight adhesion
- rubber heat-resistant up to 160°C (short-term)

### FIELD OF APPLICATION

- openings for conduits

### AVAILABLE DIMENSIONS

Article number	Type	Width	Length	for cable entry	for cable entry	Carton content
3AIRGD2	GD2	150 mm	150 mm	15 mm	20 mm	30 pieces
3AIRGD2TYP2	GD2	150 mm	150 mm	25 mm	35 mm	30 pieces
3AIRGD2TYP3	GD2	228 mm	228 mm	40 mm	55 mm	8 pieces

### TECHNICAL DATA

<b>Material composition</b>	EPDM rubber, sealing plaster with age-resistant pure acrylate adhesive	<b>Temperature resistance</b>	-40–100 °C
<b>Working temperature</b>	-5–40 °C	<b>Colour</b>	Black, sealing plaster white with green AIRSTOP imprint
<b>Age resistance of adhesive</b>	30 years	<b>Storage</b>	cool and dry

# AIRSTOP GD2 Conduit Sleeve

## INFO

Pull the rubber sleeve over the conduit and attach to the air-tight layer (vapour barrier, OSB, ...) by the integrated sealing plaster. The diameter of the sleeve selected must have the appropriate dimension for the conduit entry point! Talcum powder or a lubricant can be used if necessary to ease the feeding of the cable/pipe through the sleeve. The materials used must be free from dust and grease and substrates must be dry and supporting. The greater the pressure applied, the better the performance of the adhesive tape. On highly porous and very absorbent substrates such as concrete, plaster, untreated steel or raw wood, we recommend pre-treatment of the substrate with our ISOCELL Primers.

