



Technical data sheet



OMEGA NDB Nail Sealing Tape DSK

A bitumen tape, adhesive on both sides, that is attached along the full length between the diffusive roof underlay and the counter-batten. It prevents ingress of rainwater and guarantees optimum windtightness of the construction. Tested for protection from rain by the Austrian Wood Research Association, (Holzforschung Austria Order no. 203/2003/2 T/HH).

Advantages

- easy to use
- good adhesion on wood and underlays
- good elastic properties

Field of application

- a seal for nails and screws below the counter battens

Available dimensions

Article number	Type	Roll width	Roll length	Carton	Box / Pallet
3NDB50DSK	DSK	50 mm	10 m	6 rolls	40 cartons
3NDB60DSK	DSK	60 mm	10 m	6 rolls	40 cartons
3NDB70DSK	DSK	70 mm	10 m	6 rolls	40 cartons
3NDB80DSK	DSK	80 mm	10 m	6 rolls	40 cartons

Technical data

Material composition	self-adhesive bitumen tape	Thickness	2 mm
Temperature resistance	-40-100 °C	Working temperature	5-40 °C
Storage	1 year; cool and dry		

OMEGA NDB Nail Sealing Tape DSK

Glue the OMEGA NDB Nail Sealing Tape DSK directly to the lower side of the counter battens, then position and fix the batten. The sealing tape encloses the nail completely and achieves a 100 % sealed penetration point! See Guidelines for OMEGA Roof Underlay. The standards according to ÖNORM B 4119 and/or ZVDH (Central Association of German Roofers) must be observed.

