

## Technical data sheet



# TIMBER Protect



TIMBER Protect is a combination of fleece coated with an impermeable membrane on both sides and a specially matched polyacrylic adhesive. The tear-resistant synthetic liner facilitates handling. Construction elements can be bonded together over the entire surface with the wide sheets as protection during transport and the construction period. Joins between sheets can easily be made lengthwise along the marking grid and diagonally with 10 cm overlap.



## Advantages

- all-over self-adhesive
- transparent
- double-function membrane
- variable diffusion
- optimized re-drying of residual moisture in construction elements
- non-slip safety: anti-slip coating
- no fleece abrasion
- practical grid pattern for overlap measurement
- low heat absorption due to protection of material through light colouring
- very good self-adhesion

## Field of application

- protection for construction elements of solid wood and wooden composite materials during transport
- protection against the elements
- intermediate floors and walls
- also for use as permanent airtight layer on CLT

## Available dimensions

Article number	Roll width	Roll length	Split liner	Colour	Rolls / Pallet	Total area
3TPBZA	1.5 m	50 m	250 / 1250	Beige transparent	24 rolls	1800 m <sup>2</sup>
3TPW	1.5 m	50 m	250 / 1250	White transparent	24 rolls	1800 m <sup>2</sup>

## Technical data

sd-value	0.28-2.68 m	Material composition	PP fleece with double special membrane and anti-slip coating, special acrylic adhesive
Elongation (EN 12311-1) lengthwise	> 30 %	Elongation (EN 12311-1) crosswise	> 30 %
Tensile strength (EN 12311-1) lengthwise	>200 N/50mm	Tensile strength (EN 12311-1) crosswise	>200 N/50mm
Tear propagation resistance (EN 12310-1) lengthwise	> 50 N	Tear propagation resistance (EN 12310-1) crosswise	> 50 N
Thickness	0.33 mm	Temperature resistance	-40-70 °C
Working temperature	-5-40 °C	Weight	215 (±10%) g/m <sup>2</sup>
Resistance to water flow (EN 1928)	W1	Storage	cool and dry
Outdoor exposure	12 weeks	Fire performance (EN 13501-1 / EN 11925-0)	E

## Recommended products

	EPDM PARAPET roof gully
	EPDM roof gully DN 100
	OMEGA UNI XL Primer Spray
	OMEGA PLASTO Tape
	UNI MS Sealant Adhesive



# TIMBER Protect

## Adhesive properties

TIMBER Protect SK adopts the functions of wind and air-tightness as well as weather protection, not however the function of a load-bearing connection. TIMBER Protect SK cannot be plastered or painted over.

## Adhesive technique

TIMBER Protect SK must be bonded with the substrate over the entire surface. We recommend first cutting the required quantity to length, pulling the liner away a little and attaching the TIMBER Protect SK at one end of the construction component. The second step is to gradually pull off the liner on both sides, at the same time rubbing on the sheeting to keep it bubble-free, using e.g. a wide squeegee or wide, straight brush. The liner can be wound around a square timber and then pulled off. In this way the tension used when pulling can be evenly distributed and a crease-free and smooth bond is achieved. Overlaps of the adhesive tape should be min. 10 cm. Sufficient pressure must be applied to the open edge using a pressure roller.



## Adhesion on the following substrates

Wood, wooden composite boards (OSB, MDF, 3S-boards, chipboard, plywood...), synthetics, metal free from oxidation and rust, masonry, unsanded concrete. The materials used must be free from dust, grease and silicone, the substrates must also be dry and stable. For rough wood, similar uneven substrates, and at low temperatures, we recommend pre-treatment of the substrate with one of ISOCELL's primers. Please note that at low temperatures, and even at slight temperature changes, surface condensation may occur. This has the effect of a release layer and reduces adhesion. After applying the construction waterproofing a curing process takes place. Depending on the temperature this can take 6 - 24 hours. Only then is complete adhesion achieved.

## Tips

Walls: observe direction of water-flow. Always begin with adhesion at the bottom. Avoid open edges. Fold down at top.  
Intermediate floors: use a pressure roller in the region of edges of overlaps. If there is creasing at the edge or damage to the TIMBER Protect SK we recommend the use of OMEGA PLASTO Tape as repair tape. If available UNI MS Sealant Adhesive can also be used for repair work. Use in combination with UNI Primer Spray in the edge and overlap regions permits low working temperatures to -10° on a substrate free from ice and, when sufficient pressure is applied, increases reliability under extreme weather conditions.