

TECHNICAL DATA SHEET TINY CX



Latest technology in a small case.

The **TINY CX** is the modified successor of the Tiny Compact. In the **TINY CX**, the battery can be replaced. This causes even greater flexibility in use. If the battery is empty, the unit must not be charged. The battery is easily replaced. The **TINY CX** is delivered in a carrying case.

Machine

The **TINY CX** is a handy, battery-operated fog generator. Its easy handling and quick start-up is outstanding.

With its warming up time of less than a second, its light weight (630 grams) and the small dimensions (L=250 x W=53, H=55 mm) is applicable in many fields of operation.

In the world of theater, film, TV-and photographers, musicals and special effects, air flow and air tightness testing – everywhere where fog is needed quickly and unobtrusively, the **TINY CX** is the perfect alternative to normal fog machines.

Technology

All components of the machine have been built into small and robust housing.

Just like the TINY F07, the heart of this machine is a microprocessor which controls and supervises all important functions. This guarantees continuous and safe running of the generator.

Because of an intelligent control mechanism, the battery supplies energy only when necessary. The device is powered by a compact battery with the necessary operating voltage.

Operation

The **TINY CX** is ready to go immediately. The battery is simply inserted into the device and can be easily exchanged if necessary.

The intelligent system is the battery only supplies energy, although it is fogged. As a result, the operational readiness of the unit increased many times over traditional battery-powered machines.

The **TINY CX** can easily be triggered with one hand. The start button is placed in the lid of the machine and can be pressed with the thumb.

A special fluid ensures that dense fog is produced with the lowest fluid consumption. The vaporizer can be easily changed by the user on site.

Optional Control

The **TINY CX** can be optional controlled in the following ways:
 With the DMX-converter "DMXit" the machine can be triggered via DMX 512.
 With the timer "TIMEit" you can programme in the fogging time and the fog-free time.
 The machine can also be triggered with a radio remote control.

Technical Data

Procedure	vaporizing fog machine
Power requirement	70 Watt
Voltage	11,1 V battery
Warm up time	0,5 sec.
Fluid tank capacity	50 ml
Fluid consumption	2,3 ml/Min. with continuous output
Continuous output with internal battery	ca 15 min
Control	Startbutton Radio remote (Option) DMX 512 (Option) Timer (Option)
Temperature control	Microprocessor
Dimensions (LxWxH)	25 x 5,3 x 5,5 cm
Weight incl. battery	ca. 630 g

Package includes

- TINY CX with integrated fluid tank
- Battery 11,1 V
- 250 ml Fluid
- Carry Case

Accessories

- Radio remote
- wired remote control
- Duct Adapter
- Y-Splitter
- Silicon hose ø 15 mm
- DMX-converter
- Timer