



## ISOblow BOX TRAILER

The **ISOblow Box Trailer** is spacious, handy and robust. Its size is ideal for the transport of a blowing machine, blowing accessories and small quantities of cellulose.

Various ISOCELL templates are available for signage in combination with your company logo and address.

The trailer is lockable. Optionally, a system of shelves can be installed for small accessory parts.



# ISOCELL

### FEATURES

• Tandem trailer, braked version

- V-shaped drawbar
- Inner floor of 18mm film-faced plywood incl. adjustable. lashing
- Body of 20mm sandwich plates with polyurethane
- Maintenance-free rubber spring axles with galvanized axle tube and auto reverse
- Overhead opening of rear and side panels (incl. gas spring support)
- Version: Traversable rear ramp, white (max. load 1,000 kg)
- Customized lettering digital print

### **INTERIOR FITTINGS**

- 3 different body versions for storing blowing equipment
- Interior lighting by means of continuous LED strip n
- Automatic switch for operation via towing vehicle or external feed for lighting g
- Fastening for machine and accessories
- Electr. connection with connection boxr
- Piping and wiring







Accessories optional – not included

#### **TECHNICAL DATA**

Туре	GFK 320	GFK 420
Overrun device	up to 2.500 kg	
Load capacity	1.630 kg	1.475 kg
Dimensions (LxBxH)	4.625 x 2.110 x 2.600 mm	5.635 x 2.110 x 2.600 mm
Interior body length	3.185 mm	4.185 mm
Body height	2.085 mm	
Load height	approx. 620 mm	
Tyres	10" high quality tyres	
Item no.:	610504	610501