



Primer 9900

Primer 9900 is a adhesion promoter for porous undergrounds to improve the connection of adhesive paste 3300. It contains solvents. Primer 9900 is used on undergrounds such as concrete, metal, masonry, wood materials and wood.

ADVANTAGES

- good adhesion to many substrates
- ready for use
- rapid drying

AVAILABLE IN THE FOLLOWING DIMENSIONS

Container	Can 2,5l
-----------	----------

PRODUCT DATA

Composition	bitumen-based primer
Working temperature	ab + 5 °C
Drying time at 20°C	ca 15 min
Consumption	0,1 - 0,2l / m ²
Colour	black
Storage	approx. 12 months in closed can, cool and dry

GUIDELINES FOR USE

The underground must be clean, dry, free from grease, oil and dust. Apply Primer 9900 evenly with a brush or roller. Cleaning with Cleaner 9700 or cleaner's solvent.

08/2018_EN

ISOCELL GmbH
Gewerbestraße 9
5202 NEUMARKT AM WALLERSEE | Österreich
Tel.: +43 6216 4108 | Fax: +43 6216 7979
office@isocell.at

ISOCELL SCHWEIZ AG
Herbergstrasse 29
9524 ZUZWIL | Suisse /Schweiz
Tel.: +41 71 544 47 20
office@isocell.ch

ISOCELL FRANCE
170 Rue Jean Monnet | ZAC de Prat Pip Sud
29490 GUIPAVAS | France
Tel.: +33 2 98 42 11 00 | Fax: +33 2 98 42 11 99
contact@isocell-france.fr

ISOCELL BUREEL BELGIË
Außenborner Weg 1 | Schoppen
4770 AMEL | Belgique
Tel.: +32 80 39 90 58 | Fax: +32 80 39 97 68
office@isocell.be

ISOCELL Sverige AB
Gamla Stallet | Stora Väsbys
194 37 UPPLANDS VÄSBY | Sverige
Tel.: +46 10 130 25 01
office@isocell.se

ISOCELL
www.isocell.com