

LVD EPDM - Cellular Rubber

Takes up movements in joints and construction elements. Windproof and thermal insulation. Provides an excellent seal even under slight compression.

FIELD OF APPLICATION

- takes up movements in joints and construction elements
- Sill seal
- Wall plate Seal
- Seal between wall or roof sections SIPS
- Soundproofing

ADVANTAGES

- does not absorb water; Water has no effect on the material
- high temperature resistance
- chemically stable, uncomplicated in contact with other materials
- includes no diluents or additives, recyclable
- high resistance to aging
- windproof and thermal insulation

AVAILABLE IN THE FOLLOWING DIMENSIONS (TYP LVD)

Roll width	35 mm	70 mm	120 mm
Roll length	50 m	50 m	25 m
Thickness	10 mm	10 mm	10 mm
Rolls / Carton	6	5	6

PRODUCT DATA

Composition	EPDM – Zellkautschuk
Temperature resistance	- 40 °C - + 150 °C
Sd - value	ca. 130 m
Sealing characteristic	To seal up at 50 Pascal air pressure difference; the opening breadth has to be at most 75% of the profile height
UV- resistance	fully and permanently
Resistance to aging	> 50 years
Colour	black
Storage	cool and dry

GUIDELINES FOR USE

To attach the seal can be stapled in the middle.

10/2017_EN

ISOCELL GmbH
Gewerbestraße 9
5202 NEUMARKT AM WALLERSEE | Österreich
Tel.: +43 6216 4108 | Fax: +43 6216 7979
office@isocell.at

ISOCELL SCHWEIZ AG
Herbergstrasse 29
9524 ZUZWIL | Suisse /Schweiz
Tel.: +41 71 544 47 20
office@isocell.ch

ISOCELL FRANCE
170 Rue Jean Monnet | ZAC de Prat Pip Sud
29490 GUIPAVAS | France
Tel.: +33 2 98 42 11 00 | Fax: +33 2 98 42 11 99
contact@isocell-france.fr

ISOCELL BUREEL BELGIË
Außenborner Weg 1 | Schoppen
4770 AMEL | Belgique
Tel.: +32 80 39 90 58 | Fax: +32 80 39 97 68
office@isocell.be

ISOCELL Sverige AB
Gamla Stallet | Stora Väsby
194 37 UPPLANDS VÄSBY | Sverige
Tel.: +46 10 130 25 01
office@isocell.se

ISOCELL
www.isocell.com