



ADVANTAGES

- a stronger primer coat
- working temperature from -10° C
- resistant to + 100° C
- quick drying and economical in use
- recommended especially in winter

UNI Primer

UNI Primer is a quality, solvent-based synthetic-resin primer for preparation of the substrate to optimize the adhesive properties of cold-setting adhesive tapes, cold self-adhesive roof underlays etc. It can be used on all absorbent mineral substrates e.g. concrete, bricks, wood, etc. Advantages compared with bitumen primer: temperature resistance up to 100°C and can also be used at -10°C; it penetrates 3mm into the surface and forms a firm bond between material and adhesive; quick drying: in summer approx. 15 min., in winter 30- 45 min.;

AVAILABLE IN THE FOLLOWING DIMENSIONS

Packing	1 l	5 l
Carton / Cans	20	1

PRODUCT DATA

Drying time Summer / Winter	10 min / 30 - 45 min
Working temperature	from - 10 °C á + 35 °C
Temperature resistance	+ 100 °C
Consumption	5 m ² / Liter
Storability	12 months in closed can, Attention: it is easily inflammable

INFO :
+43 6216 / 4108
WWW.ISOCELL.COM

ISOCELL

GUIDELINES FOR USE

UNI Primer

The substrate must be level, firm, dry, free from grease, oil and dust. Apply UNI Primer evenly using a roller or a brush (spread on porous surfaces twice) and allow to dry.

Protective gloves and goggles must be worn as protection against the solvent!
Use only in ventilated places!



INFO :
+43 6216 / 4108
WWW.ISOCELL.COM

ISOCELL